

Updated

Freeform Search

Database:	<div style="border: 1px solid black; padding: 2px;"> US Pre-Grant Publication Full-Text Database US Patents Full-Text Database US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins </div>
Term:	<div style="border: 1px solid black; padding: 2px;"> (liner or lining or insulat\$3) same (embedded thermocouple or imbedded thermocouple) </div>
Display:	<div style="border: 1px solid black; padding: 2px;"> 10 Documents in Display Format: - Starting with Number 1 </div>
Generate: <input type="radio"/> Hit List <input checked="" type="radio"/> Hit Count <input type="radio"/> Side by Side <input type="radio"/> Image	

Search

Clear

Interrupt

Search History

 DATE: Friday, June 17, 2005 [Printable Copy](#) [Create Case](#)

<u>Set Name</u>	<u>Query</u>	<u>Hit Count</u>	<u>Set Name</u> result set
side by side			
	DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ		
<u>L12</u>	(liner or lining or insulat\$3) same (embedded thermocouple or imbedded thermocouple)	18	<u>L12</u>
	DB=PGPB,USPT,USOC,EPAB,JPAB; PLUR=YES; OP=ADJ		
<u>L11</u>	L9 and (liner or lining or insulati\$2)	86	<u>L11</u>
<u>L10</u>	L9 and (wear or worn or flaw or deterioration)	12	<u>L10</u>
<u>L9</u>	L8 and (thermocouple wire\$1)	125	<u>L9</u>
<u>L8</u>	(374/4,5,6,7,29,45,57,102,208,147,148,142;702/33,34,35,40.51)![CCLS]	5387	<u>L8</u>
	DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ		
<u>L7</u>	(wear detector) and (thermocouple or temperature sensor or temperature detector or thermal detector)	14	<u>L7</u>
<u>L6</u>	L5 and (resist\$4)	13	<u>L6</u>
<u>L5</u>	L3 and (wire)	29	<u>L5</u>
<u>L4</u>	L3 and (resist\$4 wire)	0	<u>L4</u>
<u>L3</u>	(wear detector) same (liner or lining)	93	<u>L3</u>
	DB=USPT; PLUR=YES; OP=ADJ		

L2 6004639.pn.

1 L2

DB=PGPB; PLUR=YES; OP=ADJ

L1 20010021360

1 L1

END OF SEARCH HISTORY